

cloud

CTP75

Be Flexible With You!



- Water-proof, Oil-proof, Dust-proof
- Built-in loudspeaker, ideal for noisy environment

Specification

Print	Print method	Direct thermal
	Print width	64/76mm
	Dot density	512/576dot/line
	Print speed	250mm/s
	Interface	Serial+USB+Ethernet
	Paper	Paper width: 79.5 ±0.5, Paper diameter: 83mm
	Line space	3.75mm(can be adjustive)
	Character Size	A NK Font Font A: 12x24dots Font B: 9x17dots Simplified/Traditional Chinese Character: 24x24dots
Barcode	Code Page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128/QRCODE
	Fonts	GB18030
Buffer	Data	128K bytes
	NV Flash	256K bytes
Power	Cashdrawer out	DC 12V/1A
	Power adapter	DC 24V/2A
	Power supply	Input: AC 110V/220V, 50~60Hz Output: DC 24/2A
Physical Properties	Weight	1.23KG
	Dimension	139x181x127mm
Environment	Work environment	Temperature:0 ~ 45°C, Humidity:10 ~ 80%
	Storage environment	Temperature:-10 ~ 60°C, Humidity:10 ~ 90%
Auto Cutter	Reliability	150km